

## Specification Sheet

Part Number: RTT750HR.NX1P



Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 25/pkg

Article Number	115-00000
Type	SpeedyTie (RTT750HR)
Color	Yellow (YE) Red (RD)
Features & Benefits	<ul style="list-style-type: none"><li>• The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.</li><li>• Additional design feature on the head allows excess strap to be tucked away after installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

<b>Short Description</b>	Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 25/pkg
<b>Global Part Name</b>	SpeedyTie (RTT750HR)-PA66-RD/YE
<b>Minimum Tensile Strength (Imperial)</b>	200.0
<b>Minimum Tensile Strength (Metric)</b>	888.0
<b>Length L (Imperial)</b>	29.6
<b>Length L (Metric)</b>	752.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.51
<b>Width W (Metric)</b>	13.0
<b>Bundle Diameter Min (Imperial)</b>	1.6
<b>Bundle Diameter Min (Metric)</b>	40.0
<b>Bundle Diameter Max (Imperial)</b>	8.3
<b>Bundle Diameter Max (Metric)</b>	210.0

**Thickness T (Imperial)**

0.075

**Thickness T (Metric)**

1.9

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

25

**Package Quantity (Metric)**

25

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

23.2

