

## Specification Sheet

Part Number: 115-00030



Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66HIRH(S), Black, 5/pkg

Article Number	115-00030
Type	SpeedyTie (RTT750HR)
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.</li><li>• Additional design feature on the head allows excess strap to be tucked away after installation.</li></ul>
Quantity Per	pcs.

### Product Description

HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

<b>Short Description</b>	Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66HIRH(S), Black, 5/pkg
<b>Global Part Name</b>	SpeedyTie (RTT750HR)-PA66HIR(S)-BK
<b>Minimum Tensile Strength (Imperial)</b>	200.0
<b>Minimum Tensile Strength (Metric)</b>	888.0
<b>Length L (Imperial)</b>	29.6
<b>Length L (Metric)</b>	752.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.51
<b>Width W (Metric)</b>	13.0
<b>Bundle Diameter Min (Imperial)</b>	1.6
<b>Bundle Diameter Min (Metric)</b>	40.0
<b>Bundle Diameter Max (Imperial)</b>	8.3
<b>Bundle Diameter Max (Metric)</b>	210.0

<b>Thickness T (Imperial)</b>	0.075
<b>Thickness T (Metric)</b>	1.9
<b>Material</b>	Polyamide 6.6, high impact modified, scan black (PA66HIR(S))
<b>Material Shortcut</b>	PA66HIR(S)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +176°F (-40°C to +80°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	5
<b>Package Quantity (Metric)</b>	5
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	23.2

