

Specification Sheet

Part Number: RT150REP0X2



Releasable Cable Tie, Release Tab, 15.4" Long, 175lb Tensile Strength, PA66, Black, 25/pkg

| | |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number | 115-00036 |
| Type | RT150REP |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Special design with extended pawl offers a release feature for quick and easy access to wire bundles.• Head design provides high tensile strength with very low insertion force even after repeated use. |
| Quantity Per | bag |

Product Description

HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--------------------------------------------|--------------------------------------------------------------------------------------------|
| Short Description | Releasable Cable Tie, Release Tab, 15.4" Long, 175lb Tensile Strength, PA66, Black, 25/pkg |
| Global Part Name | RT150REP-PA66-BK |
| Minimum Tensile Strength (Imperial) | 175.0 |
| Minimum Tensile Strength (Metric) | 780.0 |
| Length L (Imperial) | 15.4 |
| Length L (Metric) | 390.0 |
| Identification Plate Position | none |
| Releasable Closure | Yes |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.35 |
| Width W (Metric) | 8.8 |
| Bundle Diameter Min (Imperial) | 0.32 |
| Bundle Diameter Min (Metric) | 8.0 |
| Bundle Diameter Max (Imperial) | 4.1 |
| Bundle Diameter Max (Metric) | 105.0 |

| | |
|---------------------------------------|----------------------------------|
| Cable Tie Width Max (Imperial) | 0.35 |
| Cable Tie Width Max (Metric) | 8.8 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 25 |
| Package Quantity (Metric) | 25 |
| Customs Number | 3926909987 |