

Specification Sheet

Part Number: DCT90HIRC2



Provides dual separation between bundles to prevent chafing and abrasion.

150lb. tensile strength ensures enough strength for heavy duty applications.

Straps are releasable for increased serviceability.

Dual Clamp Tie, 13" Long, 0.25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black, 100/pkg

Article Number 115-00136

Type DCT9

Color Black (BK)

Quantity Per bag

Product Description Dual-Clamp Ties are designed to provide parallel separation between hoses, wires, cables, and tubing to protect them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of trucks, trailers, and heavy-duty equipment. The unique one-piece design features the dual head centered on the strap.

Short Description Dual Clamp Tie, 13" Long, 0.25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black, 100/pkg

Global Part Name DCT9-PA66HIRHSUV-BK

| | |
|-------------------------------------|------------------|
| Minimum Tensile Strength (Imperial) | 150 |
| Minimum Tensile Strength (Metric) | 667 |
| Length L (Imperial) | 13.0 |
| Length L (Metric) | 331.0 |
| Fixation Method | Weld Stud Fixing |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.5 |
| Width W (Metric) | 12.7 |
| Bundle Diameter Min (Imperial) | 0.25 |
| Bundle Diameter Min (Metric) | 6.4 |
| Bundle Diameter Max (Imperial) | 1.3 |
| Bundle Diameter Max (Metric) | 33.0 |
| Height H (Imperial) | 0.8 |

| | |
|------------------------------|--|
| Height H (Metric) | 19.1 |
| Stud Diameter (Metric) | M6 |
| Stud Diameter (Imperial) | 1/4 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |
| Weight (Metric) | 12.0 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).