

## Specification Sheet

Part Number: SR255X0HIHSUVC2



Releasable Cable Tie, 14.6" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 100/pkg

Article Number	115-00157
Type	SR255X
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.</li><li>• Special design offers a release feature for quick and easy access to wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li></ul>
Quantity Per	bag
Product Description	HellermannTyton SR255 Series heavy-duty cable ties offer a release feature in the head allowing for easy installation with the use of a cable tie tool. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force.

<b>Short Description</b>	Releasable Cable Tie, 14.6" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 100/pkg
<b>Global Part Name</b>	SR255X-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	250.0
<b>Minimum Tensile Strength (Metric)</b>	1115.0
<b>Length L (Imperial)</b>	14.6
<b>Length L (Metric)</b>	370.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.6
<b>Bundle Diameter Min (Imperial)</b>	0.51
<b>Bundle Diameter Min (Metric)</b>	13.0
<b>Bundle Diameter Max (Imperial)</b>	3.9
<b>Bundle Diameter Max (Metric)</b>	100.0
<b>Cable Tie Width Max (Imperial)</b>	0.49

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100