

## Specification Sheet

Part Number: 117-00008



Heat stabilized cable ties provide excellent resistance to high heat exposures.

The tie contains a dual locking design to secure two bundles at once.

Head design can also provide spacing between parallel bundles.

Bent tail allows for quick insertion into head.

Double-Head Cable Tie, 15.6" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

**Article Number** 117-00008

**Type** T50LDH

**Color** Black (BK)

**Quantity Per** bag

**Product Description** The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Double-Head Cable Tie, 15.6" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

**Global Part Name** T50LDH-PA66HS-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 15.6

**Length L (Metric)** 395.0

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.19

**Width W (Metric)** 4.7

**Bundle Diameter Min (Imperial)** 0.06

**Bundle Diameter Min (Metric)** 1.6

**Bundle Diameter Max (Imperial)** 4.0

**Bundle Diameter Max (Metric)** 100

**Bundle Diameter 1st Loop Max (Imperial)** 4.0

**Bundle Diameter 2nd Loop Max (Imperial)** 2.0

**Thickness T (Imperial)** 0.055

**Thickness T (Metric)** 1.4

**Cable Tie Head Length (Imperial)** 0.53

**Cable Tie Head Width (Imperial)** 0.32

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL 94 V2

**Halogen Free** Yes

**Operating Temperature** -40°F to +257°F (-40°C to +125°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Certification/Specification** UL | ANSI/UL 1565 UL | ANSI/UL 746B UL | ANSI/UL 62275

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988