

Specification Sheet

Part Number: 117-00008

Heat stabilized cable ties provide excellent resistance to high heat exposures

Head design contains clamping rails to provide full circumferential compression around bundles

Bent tail allows for quick insertion into head



Double-Head Cable Tie, 15.6" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

Article Number 117-00008

Type T50LDH

Color Black (BK)

Quantity Per bag

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Double-Head Cable Tie, 15.6" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

Global Part Name T50LDH-PA66HS-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225.0

Length L (Imperial) 15.6

Length L (Metric) 395.0

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 4.0

Bundle Diameter Max (Metric) 100

Bundle Diameter 1st Loop Max (Imperial) 4.0

Bundle Diameter 2nd Loop Max (Imperial) 2.0

Thickness T (Imperial) 0.055

Thickness T (Metric) 1.4

Cable Tie Head Length (Imperial) 0.53

Cable Tie Head Width (Imperial) 0.32

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V-2

Halogen Free Yes

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL | ANSI/UL 62275 UL | ANSI/UL 1565 UL | ANSI/UL 746B

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988