


Specification Sheet

Part Number: T50RDH0UVC2



Double-Head Cable Tie, 8.3" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number	117-05011
Type	T50RDH
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• The tie contains a dual locking design to secure two bundles at once.• Head design can also provide spacing between parallel bundles.• Bent tail allows for quick insertion into head.
Quantity Per	bag

Product Description

The double head cable tie was designed with a dual locking head that creates two loops to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Double-Head Cable Tie, 8.3" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg
Global Part Name	T50RDH-PA66UV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.3
Length L (Metric)	210.82
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	38.0

Bundle Diameter 1st Loop Max (Imperial)	1.7
Bundle Diameter 1st Loop Max (Metric)	44.4
Bundle Diameter 2nd Loop Max (Imperial)	0.75
Bundle Diameter 2nd Loop Max (Metric)	19.0
Thickness T (Imperial)	0.055
Thickness T (Metric)	1.4
Cable Tie Head Length (Imperial)	0.53
Cable Tie Head Width (Imperial)	0.32
Material	Polyamide 6.6 UV-stabilized (PA66UV)
Material Shortcut	PA66UV
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909988