

Specification Sheet

Part Number: T120RDH0H4



Double-Head Cable Tie, 15.7" Long, 120lb Tensile Strength, PA66, Black, 500/pkg

Article Number	117-05500
Type	T120RDH
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• The tie contains a dual locking design to secure two bundles at once.• Head design can also provide spacing between parallel bundles.• Bent tail allows for quick insertion into head.
Quantity Per	bag

Product Description

The double head cable tie was designed with a dual locking head that creates two loops to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Double-Head Cable Tie, 15.7" Long, 120lb Tensile Strength, PA66, Black, 500/pkg
Global Part Name	T120RDH-PA66-BK
Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535.0
Length L (Imperial)	15.7
Length L (Metric)	398.0
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.3
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.19
Bundle Diameter Min (Metric)	4.6
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.8
Bundle Diameter 1st Loop Max (Imperial)	4.0

Bundle Diameter 1st Loop Max (Metric)

101.6

Bundle Diameter 2nd Loop Max (Imperial)

2.0

Bundle Diameter 2nd Loop Max (Metric)

50.8

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

Flammability

UL 94 V2

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ2.E64139

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909988

