

Specification Sheet

Part Number: T120RDH0H4



Double-Head Cable Tie, 15.7" Long, 120lb Tensile Strength, PA66, Black, 500/pkg

Article Number 117-05500

Type T120RDH

Color Black (BK)

Features & Benefits

- The tie contains a dual locking design to secure two bundles at once.
- Head design can also provide spacing between parallel bundles.
- Bent tail allows for quick insertion into head.

Quantity Per bag

Product Description

The double head cable tie was designed with a dual locking head that creates two loops to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--|---|
| Short Description | Double-Head Cable Tie, 15.7" Long, 120lb Tensile Strength, PA66, Black, 500/pkg |
| Global Part Name | T120RDH-PA66-BK |
| Minimum Tensile Strength (Imperial) | 120.0 |
| Minimum Tensile Strength (Metric) | 535.0 |
| Length L (Imperial) | 15.7 |
| Length L (Metric) | 398.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.3 |
| Width W (Metric) | 7.6 |
| Bundle Diameter Min (Imperial) | 0.18 |
| Bundle Diameter Min (Metric) | 4.6 |
| Bundle Diameter Max (Imperial) | 4.0 |
| Bundle Diameter Max (Metric) | 101.6 |

Bundle Diameter 1st Loop Max (Imperial) 4.0

Bundle Diameter 1st Loop Max (Metric) 101.6

Bundle Diameter 2nd Loop Max (Imperial) 2.0

Bundle Diameter 2nd Loop Max (Metric) 50.8

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 V2

Operating Temperature (Metric) -40°F to +185°F (-40°C to +85°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL-ZODZ2.E64139

Use Conditions For Indoor Use Only

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

Content Unit(BMEcat) pcs.