

Specification Sheet

Part Number: T18RA50HSW



Cable Tie for AT2000, 18lb Tensile Strength, PA66HS, Black, 50/bandolier, 500/pkg

| | |
|---------------------|--|
| Article Number | 120-05003 |
| Type | T18RA50 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Cable ties can be easily recycled to meet environmental management objectives.•HellermannTyton 18 lb. cable ties are available in natural, black, and other colors (upon request) to support color coded wire management schemes.•Bandoliers of 50 or reels of 5000 cable ties are available, enabling maximum user efficiency in hand-held, bench-mount, or automated processes. |
| Quantity Per | bag |

Product Description

HellermannTyton's AT2000 is designed to use 18 lb. cable ties and will fasten bundles up to 3/4" diameter. Engineered specifically for automatic cable tie assembly, these ties are offered in varying material compositions and colors, so manufacturers can select the ties that meet the application requirements and industry best practices.

Short Description

Cable Tie for AT2000, 18lb Tensile Strength, PA66HS, Black, 50/bandolier, 500/pkg

Global Part Name

T18RA50-PA66HS-BK

Technical Description

Cable Tie for AT2000, Black, 50/bandolier

Minimum Tensile Strength (Imperial)

18.0

Minimum Tensile Strength (Metric)

80.0

Length L (Imperial)

4.0

Length L (Metric)

4.8

Width W (Imperial)

0.1

Width W (Metric)

2.5

Bundle Diameter Min (Imperial)

0.03

Bundle Diameter Min (Metric)

0.7

Bundle Diameter Max (Imperial)

0.79

Bundle Diameter Max (Metric)

20.0

Power supply unit

Electrical

Material

Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut

PA66HS

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +257°F (-40°C to +125°C)

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909988