

Specification Sheet

Part Number: 126-00080



Push Mount Tie with Seal, 6.2" Long, Mounting Hole Diameter 0.24"-0.48", PA66HS, Black, 500/pkg

Article Number	126-00080
Type	T60SOSSFT62x122-E-MD
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•Design helps silence and stabilize the tie in high-vibration applications.•Arrowhead-style mount provides low insertion and high extraction force.•Anti-rotational oval fastener forces bundle to travel in intended direction.•Rubber seal restricts water and debris from passing through mounting hole.
Quantity Per	bag
Product Description	Push Mount Ties with Seal for Oval Holes provide a one-piece bundling and mounting solution. The oval arrowhead fastener won't rotate once inserted into a panel hole, ensuring proper routing of wires and hoses. The welded rubber seal protects against the ingress of water and debris.

Short Description

Push Mount Tie with Seal, 6.2" Long, Mounting Hole Diameter 0.24"-0.48", PA66HS, Black, 500/pkg

Global Part Name

T60SOSSFT62x122-E-MD-PA66HS-BK

Minimum Tensile Strength (Imperial)

67.0

Minimum Tensile Strength (Metric)

300

Length L (Imperial)

6.2

Length L (Metric)

157.5

Fixation Method

Arrowhead for oval holes

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.22

Width W (Metric)

5.5

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.6

Bundle Diameter Max (Imperial)

1.18

Bundle Diameter Max (Metric)	30.0
Thickness T (Metric)	1.35
Panel Thickness Min(Imperial)	0.023
Panel Thickness Max(Imperial)	0.079
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.48
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.48
Mounting Hole Diameter D Max (Metric)	12.2
Disc Diameter(Metric)	16.0 x 22.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

Content Unit(BMEcat) pcs.

Weight (Metric) 2.05