

Specification Sheet

Part Number: 126-00099



All-in-one bundling and mounting solution reduces costs.
Low-profile design provides dependable cable management in tight spaces.

1-Piece Cable Tie/Fir Tree Mount, 6.1" Long, Mounting Hole Diameter .19"-.21", PA66HS, Black, 1000/pkg

Article Number	126-00099
Type	T50SOSSFT5S-E
Color	Black (BK)
Quantity Per	bag
Product Description	The low-profile push mount design provides an overall shortened length, which assists in limiting protrusion on the opposing side of application surfaces. The mount's rounded tip allows for a smoother surface in case of contact with surrounding components or hands. The dome provides firm, rattle-free performance and keeps out debris. One-piece mounting ties offer a complete solution by both bundling and mounting.
Short Description	1-Piece Cable Tie/Fir Tree Mount, 6.1" Long, Mounting Hole Diameter .19"-.21", PA66HS, Black, 1000/pkg

Global Part Name T50SOSSFT5S-E-PA66HS-BK

Minimum Tensile Strength (Imperial) 40.0

Minimum Tensile Strength (Metric) 180

Length L (Imperial) 6.0

Length L (Metric) 156.0

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.4

Bundle Diameter Max (Metric) 35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.05
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	1.3
Mounting Hole Diameter D (Imperial)	0.19 - 0.21
Mounting Hole Diameter D (Metric)	4.8 - 5.2 mm
Mounting Hole Diameter D Min (Imperial)	0.19
Mounting Hole Diameter D Max (Imperial)	0.21
Mounting Hole Diameter D Max (Metric)	5.2
Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.63

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability	UL 94 V-2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Minimum Extraction Force (Imperial)	40.0
Minimum Extraction Force (Metric)	180
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988