

Specification Sheet

Part Number: 126-00245



Design helps silence and stabilize the tie in high-vibration applications. Arrowhead-style mount provides low insertion and high extraction force. Rubber seal restricts water and debris from passing through mounting hole.

1-Piece Cable Tie/Arrowhead Mount with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bag

Article Number 126-00245

Type T50SOSSFT6.5E-MS-MD

Color Natural (NA)

Quantity Per bag

Product Description

The arrowhead design of these ties offers a positive, low insertion force and a high extraction force. These ties feature a foam rubber seal which provides additional protection against moisture, dirt, and other impurities. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description	1-Piece Cable Tie/Arrowhead Mount with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bag
Global Part Name	T50SOSSFT6.5E-MS-MD-PA66HS-NA
Minimum Tensile Strength (Imperial)	40.5
Minimum Tensile Strength (Metric)	180.0
Length L (Imperial)	6.5
Length L (Metric)	163.0
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5

Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	0.63
Height H (Metric)	16.0
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.07
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	1.8
Mounting Hole Diameter D (Imperial)	0.25 - 0.27
Mounting Hole Diameter D (Metric)	6.35 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.9
Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.63

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V2

Operating Temperature -40°F to +257°F (-40°C to +125°C)

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988