

## Specification Sheet

Part Number: 126-00326



1-Pc Cable Tie/Arrowhead Mount w/Disc, 6.2"L, 0.25" - 0.26" Hole Dia, PA66HS, Black, 500/pkg

Article Number	126-00326
Type	T50SOSKSFT6.5S2-E
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Dome provides a tight, rattle-free installation.</li><li>• Outside serrated strap has ribs designed for convoluted tubing.</li><li>• Dome acts as a seal to keep out dust and liquid.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton's low profile push mount design provides an overall shortened length which assists in limiting protrusion on the opposing side of application surfaces. The rounded tip of the mount allows for a smoother surface in case of contact with surrounding components or human touch during service.

<b>Short Description</b>	1-Pc Cable Tie/Arrowhead Mount w/Disc, 6.2"L, 0.25" - 0.26" Hole Dia, PA66HS, Black, 500/pkg
<b>Global Part Name</b>	T50SOSKSFT6.5S2-E-PA66HS-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	157.0
<b>Fixation Method</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Outside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.04
<b>Bundle Diameter Min (Metric)</b>	1.0
<b>Bundle Diameter Max (Imperial)</b>	1.4

<b>Bundle Diameter Max (Metric)</b>	35.0
<b>Thickness T (Imperial)</b>	0.05
<b>Thickness T (Metric)</b>	1.3
<b>Height H (Imperial)</b>	0.58
<b>Height H (Metric)</b>	14.732
<b>Panel Thickness Min(Imperial)</b>	0.07
<b>Panel Thickness Max(Imperial)</b>	0.09
<b>Panel Thickness Min (Metric)</b>	1.7
<b>Panel Thickness Max (Metric)</b>	2.3
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.7 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.25
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.7
<b>Disc Diameter(Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	1.3