

Specification Sheet

Part Number: 126-00360



Push Mount Arrowhead Tie Wings, Panel Thickness .24" - .26", 5.3" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag

| | |
|---------------------|---|
| Article Number | 126-00360 |
| Type | T50SSL5 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.•Arrowhead style mount provides low insertion and high extraction force.•Arrowhead disc protects against dirt and other impurities. |
| Quantity Per | pcs. |

Product Description

Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

| | |
|--|---|
| Short Description | Push Mount Arrowhead Tie Wings, Panel Thickness .24" - .26", 5.3" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag |
| Global Part Name | T50SSL5-PA66HS-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 200 |
| Length L (Imperial) | 5.3 |
| Length L (Metric) | 135 |
| Fixation Method | Arrowhead |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.5 |
| Bundle Diameter Max (Imperial) | 1.0 |

| | |
|--|--|
| Bundle Diameter Max (Metric) | 27.0 |
| Height H (Imperial) | 0.4 |
| Height H (Metric) | 10 |
| Panel Thickness Min(Imperial) | 0.019 |
| Panel Thickness Max(Imperial) | 0.11 |
| Panel Thickness Min (Metric) | 0.5 |
| Panel Thickness Max (Metric) | 2.7 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.26 |
| Mounting Hole Diameter D (Metric) | 6.1 - 6.5 mm |
| Mounting Hole Diameter D Max (Metric) | 6.5 |
| Disc Diameter (Imperial) | 0.64 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| Reach Complaint(Article 33) | Yes |

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

Weight (Metric)

1.2