

Specification Sheet

Part Number: T50RSF0C2



1-Piece Cable Tie/Arrowhead Mount, 8.3"L, 50lb, 0.04"–0.14" Panel Thickness, PA66HS, Black, 100/pkg

| | |
|---------------------|---|
| Article Number | 126-01003 |
| Type | T50RSF(U) |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•All-in-one bundling and fastening solution reduces costs and assembly time.•The arrowhead design of these ties offers a low insertion force and a high extraction force.•High-spec materials and superior design deliver versatility, performance and value. |
| Quantity Per | bag |

Product Description

One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. The arrowhead design of this push mount inserts easily and locks securely in place. HellermannTyton's one-piece mounting ties combine high-specification materials with superior design to deliver dependable performance in a range of applications.

| | |
|--|---|
| Short Description | 1-Piece Cable Tie/Arrowhead Mount, 8.3"L, 50lb, 0.04"-0.14" Panel Thickness, PA66HS, Black, 100/pkg |
| Global Part Name | T50RSF(U)-PA66HS-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 8.3 |
| Length L (Metric) | 210.0 |
| Fixation Method | Arrowhead |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.19 |
| Width W (Metric) | 4.7 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.6 |
| Bundle Diameter Max (Imperial) | 1.7 |

| | |
|--|----------------------|
| Bundle Diameter Max (Metric) | 44.0 |
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.2 |
| Height H (Imperial) | .30 |
| Height H (Metric) | 7.50 |
| Panel Thickness Min(Imperial) | 0.039 |
| Panel Thickness Max(Imperial) | 0.14 |
| Panel Thickness Min (Metric) | 1.0 |
| Panel Thickness Max (Metric) | 3.56 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.28 |
| Mounting Hole Diameter D (Metric) | 6.4 - 7.1 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.28 |
| Mounting Hole Diameter D Max (Metric) | 7.1 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66HS |

| | |
|--|-----------------------------------|
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL-ZODZ2.E64139 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909987 |