

Specification Sheet

Part Number: 126-02600

Arrowhead design is quick and easy to install by hand without the need for a tool.



Ties "clicks" into place upon final installation signaling installer insertion is complete.

Design provides low insertion and high extraction force.

1-Piece Cable Tie/Arrowhead Mount with Wings in the Strap, 8.0" L, Hole Dia .24" - .26", PA66HS, Black, 1000/pkg

Article Number 126-02600

Type T80RSF6.5F

Color Black (BK)

Quantity Per pcs.

Product Description Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor slides along the tie and adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Short Description 1-Piece Cable Tie/Arrowhead Mount with Wings in the Strap, 8.0" L, Hole Dia .24" - .26", PA66HS, Black, 1000/pkg

Global Part Name T80RSF6.5F-PA66HS-BK

Minimum Tensile Strength (Imperial)	80
Minimum Tensile Strength (Metric)	355
Length L (Imperial)	8.0
Length L (Metric)	209
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.7
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Metric)	1.3
Height H (Imperial)	0.05
Height H (Metric)	1.3

Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.02
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.3 - 6.5 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.5
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000

Package Quantity (Metric) 1000

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)