

Specification Sheet

Part Number: 133-00059



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

1-Piece Cable Tie & Edge Clip, 3.5" Long, EC5, Panel Thickness 0.04 - 0.12", 50 lb, PA66HS, Black, 500/bg

Article Number 133-00059

Type T40XEC5SP-E

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Cable Tie with Edge Clip is designed to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure, and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. This fastener is molded as a one-piece clip and tie combination.

Short Description 1-Piece Cable Tie & Edge Clip, 3.5" Long, EC5, Panel Thickness 0.04 - 0.12", 50 lb, PA66HS, Black, 500/bg

Global Part Name T40XEC5SP-E-PA66HS-BK

Minimum Tensile Strength (Imperial) 40

Minimum Tensile Strength (Metric) 178

Length L (Imperial) 3.5

Length L (Metric) 85.0

Fixation Method Edge Clip

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.16

Width W (Metric) 4.0

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 0.6

Bundle Diameter Max (Metric) 15.0

Height H (Imperial) 0.05

Height H (Metric) 1.2

Panel Thickness Min (Imperial) 0.04

Panel Thickness Max (Imperial) 0.12

Panel Thickness Min (Metric) 1.0

Panel Thickness Max (Metric) 3.0

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V-2

UV Resistant (Yes/No) No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number

3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)