

Specification Sheet

Part Number: 133-02792

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.



Connector Clip w/Round Fir Tree, 1.5 - 5.0 mm Panel Thickness, PA66HIRHS, Black, 1500/carton

Article Number	133-02792
Type	CC7DBLFT6.5TS5
Color	Black (BK)
Quantity Per	carton
Product Description	Connector clips feature various attachment point configurations to accommodate the many connectors on the market. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
Short Description	Connector Clip w/Round Fir Tree, 1.5 - 5.0 mm Panel Thickness, PA66HIRHS, Black, 1500/carton

Global Part Name CC7DBLFT6.5TS5-PA66HIRHS-BK

Length L (Imperial) 1.63

Length L (Metric) 41.5

Fixation Method Fir tree for round holes

Width W (Imperial) 0.98

Width W (Metric) 24.8

Height H (Imperial) 0.73

Height H (Metric) 18.61

Panel Thickness Min (Imperial) 0.06

Panel Thickness Max (Imperial) 0.20

Panel Thickness Min (Metric) 1.5

Panel Thickness Max (Metric) 5.0

Mounting Hole Diameter D (Imperial) 0.30 - 0.31

Mounting Hole Diameter D (Metric) 7.7 - 7.85 mm

Mounting Hole Diameter D Min (Imperial) 0.30

Mounting Hole Diameter D Max (Imperial) 0.31

Mounting Hole Diameter D Max (Metric) 7.85

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

UV Resistant (Yes/No) Yes

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Package Quantity (Imperial) 1500

Package Quantity (Metric) 2500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)