

## Specification Sheet

Part Number: 133-03178



Tube and Pipe Clip with 6.5mm Arrowhead, 4.7-5.1mm Diameter, PA66HIRHS, Black, 4000/ctn

**Article Number** 133-03178

**Type** PC5AH6.5

**Color** Black (BK)

**Features & Benefits**

- Inverted retaining legs and narrow opening prevent inadvertent disengagement.
- Controlled flex and angled entry promote easy installation.
- Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 6.5 mm hole in panels from 1.2 to 1.6 mm.

**Quantity Per** carton

**Product Description** This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.

<b>Short Description</b>	Tube and Pipe Clip with 6.5mm Arrowhead, 4.7-5.1mm Diameter, PA66HIRHS, Black, 4000/ctn
<b>Global Part Name</b>	PC5AH6.5-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	0.67
<b>Length L (Metric)</b>	17.0
<b>Fixation Method</b>	Arrowhead
<b>Width W (Metric)</b>	10.0
<b>Height H (Imperial)</b>	0.86
<b>Height H (Metric)</b>	21.5
<b>Panel Thickness Min (Imperial)</b>	0.05
<b>Panel Thickness Max (Imperial)</b>	0.06
<b>Panel Thickness Min (Metric)</b>	1.2
<b>Panel Thickness Max (Metric)</b>	1.6
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.9 mm 6.35 mm (hexagonal)
<b>Disc Diameter (Metric)</b>	17.0

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	4000
<b>Package Quantity (Metric)</b>	4000
<b>Customs Number</b>	3926909988