

Specification Sheet

Part Number: 148-90037



HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 3-Port, (PC), Orange, 100/pkg

Article Number

148-90037

Type

HCPM-3

Color

Clear (CL) Orange (OG)

Features & Benefits

- Spring technology for safe, secure and reliable connections.
- Smaller footprint fits in tight spaces.
- Low insertion force makes installation of solid or stranded copper wire fast and easy.
- Color coded for easy identification of size.
- Each port accepts multiple wire diameters for flexible applications.
- Accepts 12–22 AWG solid wire and 14–22 AWG stranded wire.

Quantity Per

box

Product Description

HelaCon Plus Mini Wire Connectors replace traditional twist-on wire connectors. They provide faster, easier and more reliable connection and distribution of cable and conductors in electrical installation applications. Mini connectors have a compact footprint and can be applied tool-free using convenient, push-in simplicity. Internal spring technology is approved for solid and stranded wires.

Short Description

HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 3-Port, (PC), Orange, 100/pkg

Global Part Name

HCPM-3-PC-CL/OG

Length L (Imperial)

0.65

Length L (Metric)

16.5

Width W (Imperial)

0.59

Width W (Metric)

15.1

Height H (Imperial)

0.30

Height H (Metric)

7.70

Depth D (imperial)

0.65

Depth D (metric)

16.5

Material

Polycarbonate (PC)

Material Shortcut

PC

Flammability

UL 94 V0

Halogen free

Yes

Operating Temperature (Metric)

-22°F to +185°F (-30°C to +85°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB SGS Fimko Ltd | EN 60998-2-2:201 Intertek Semko | EN 60998-2-2:2004 NEMKO AS | EN 60998-2-2:2004 UL | ANSI/UL 486-A UL | ANSI/UL 486-B UL | ANSI/UL 486-C SGS Fimko Ltd | EN 60998-2-2:2004 cULus CE | 2006/65/EC ENEC

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988

Content Unit(BMEcat) pcs.