

## Specification Sheet

Part Number: 150-37791



2-Piece Cable Tie/Arrowhead Mount, 6.5mm hole dia., 0.6-8.25mm Panel Thickness, PA66HIRHS, Black, 500/bag

**Article Number**

150-37791

**Type**

T50ROSSFT6.5 16-3

**Color**

Black (BK)

**Features & Benefits**

- Two-piece assembly allows mount to slide along strap, ensuring proper orientation.
- Arrowhead-style mount provides low insertion and high extraction force.
- Multiple material options provide solutions for any environment.

**Quantity Per**

bag

**Product Description**

HellermannTyton's Arrowhead Push Mount Tie Assembly is a two piece design allowing the mount to slide along the strap of the tie to ensure proper orientation. The arrowhead mount is designed for low insertion into a pre-drilled hole, while providing a high extraction force. The disc also protects against dirt and other impurities.

**Short Description**

2-Piece Cable Tie/Arrowhead Mount, 6.5mm hole dia., 0.6-8.25mm Panel Thickness, PA66HIRHS, Black, 500/bag

**Global Part Name**

T50ROSSFT6.5 16-3-PA66HS/PA66HIRHS-BK

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

7.87

**Length L (Metric)**

200

**Fixation Method**

Arrowhead

**Identification Plate Position**

none

**Tie Closure**

plastic pawl

**Variant**

Outside Serrated

**Width W (Imperial)**

0.181

**Width W (Metric)**

4.6

**Bundle Diameter Min (Imperial)**

0.197

**Bundle Diameter Min (Metric)**

5.0

**Bundle Diameter Max (Imperial)**

1.77

**Bundle Diameter Max (Metric)**

45.0

<b>Height H (Imperial)</b>	0.051
<b>Height H (Metric)</b>	1.3
<b>Panel Thickness Min(Imperial)</b>	0.098
<b>Panel Thickness Max(Imperial)</b>	0.138
<b>Panel Thickness Min (Metric)</b>	2.5
<b>Panel Thickness Max (Metric)</b>	3.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.248 - 0.264
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.7 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.248
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.7
<b>Disc Diameter(Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS

<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.9