

## Specification Sheet

Part Number: 150-48396

Arrowhead design is quick and easy to install by hand without the need for tools.

Ties "clicks" into place upon final installation signaling installer insertion is complete.

Design provides low insertion and high extraction force.



1-Pc Cable Tie/Arrowhead Mount w/Wings for Oval Holes, 9.0"L, 50lb Tensile, PA66, Black, 1000/bag

<b>Article Number</b>	150-48396
<b>Type</b>	T80RFT6X12
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.
<b>Short Description</b>	1-Pc Cable Tie/Arrowhead Mount w/Wings for Oval Holes, 9.0"L, 50lb Tensile, PA66, Black, 1000/bag
<b>Global Part Name</b>	T80RFT6X12-PA66-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	222
<b>Length L (Imperial)</b>	9.0
<b>Length L (Metric)</b>	228
<b>Fixation Method</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.181
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.8
<b>Bundle Diameter Max (Metric)</b>	45.0
<b>Panel Thickness Min (Imperial)</b>	0.02

<b>Panel Thickness Max (Imperial)</b>	0.02
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.48
<b>Mounting Hole Diameter D (Metric)</b>	6.3 x 12.3 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.248
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.48
<b>Mounting Hole Diameter D Max (Metric)</b>	12.3
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988