

## Specification Sheet

Part Number: 150-48396



Arrowhead design is quick and easy to install by hand without the need for tools.

Ties "clicks" into place upon final installation signaling installer insertion is complete.

Design provides low insertion and high extraction force.

1-Pc Cable Tie/Arrowhead Mount w/Wings for Oval Holes, 9.0"L, 50lb Tensile, PA66, Black, 1000/bag

Article Number 150-48396

Type T80RFT6X12

Color Black (BK)

Quantity Per bag

Product Description Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Short Description 1-Pc Cable Tie/Arrowhead Mount w/Wings for Oval Holes, 9.0"L, 50lb Tensile, PA66, Black, 1000/bag

Global Part Name T80RFT6X12-PA66-BK

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	222
Length L (Imperial)	9.0
Length L (Metric)	228
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.181
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.8
Bundle Diameter Max (Metric)	45.0
Panel Thickness Min (Imperial)	0.02

Panel Thickness Max (Imperial)	0.02
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.25 - 0.48
Mounting Hole Diameter D (Metric)	6.3 x 12.3 mm
Mounting Hole Diameter D Min (Imperial)	0.248
Mounting Hole Diameter D Max (Imperial)	0.48
Mounting Hole Diameter D Max (Metric)	12.3
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988