

## Specification Sheet

Part Number: 150-55500



1-Piece Cable Tie/Fir Tree Mount, 6.7" Long, Mounting Hole Diameter 0.25" - 0.28", PA66, Black, 500/pkg

**Article Number** 150-55500

**Type** REL30SDP6

**Color** Black (BK)

**Features & Benefits**

- An all-in-one bundling and mounting solution that reduces parts and costs.
- High-specification materials and superior design suit the bundling and fastening requirements of complex applications.
- Release feature allows maintenance or changeouts as needed.

**Quantity Per** bag

**Product Description**

The releasable cable tie with fir tree mount offers a complete bundling and fastening solution. The extended pawl allows the user to release the tie for bundle maintenance. HellermannTyton's one-piece mounting ties deliver the ideal combination of high-specification materials and superior design.

<b>Short Description</b>	1-Piece Cable Tie/Fir Tree Mount, 6.7" Long, Mounting Hole Diameter 0.25" - 0.28", PA66, Black, 500/pkg
<b>Global Part Name</b>	REL30SDP6-PA66-BK
<b>Minimum Tensile Strength (Imperial)</b>	30.0
<b>Minimum Tensile Strength (Metric)</b>	135
<b>Length L (Imperial)</b>	6.7
<b>Length L (Metric)</b>	170.0
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.2
<b>Width W (Metric)</b>	5.0
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5

<b>Bundle Diameter Max (Imperial)</b>	1.2
<b>Bundle Diameter Max (Metric)</b>	31.0
<b>Thickness T (Imperial)</b>	0.06
<b>Thickness T (Metric)</b>	1.5
<b>Height H (Imperial)</b>	0.5
<b>Panel Thickness Min (Imperial)</b>	0.12
<b>Panel Thickness Max (Imperial)</b>	0.28
<b>Panel Thickness Min (Metric)</b>	3.0
<b>Panel Thickness Max (Metric)</b>	7.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 7.1 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.25
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28
<b>Mounting Hole Diameter D Max (Metric)</b>	7.1
<b>Disc Diameter (Metric)</b>	22.0
<b>Disc Diameter (Imperial)</b>	0.87

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	3.2