

Specification Sheet

Part Number: MMB.50C2



Masonry Cable Tie Mount, 1.24"L, .25" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 100/pkg

Article Number 151-00116

Type MMB.5

Color Black (BK)

Features & Benefits

- Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces.
- The mounts have easy installation into predrilled holes allowing for faster use.

Quantity Per bag

Product Description

HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.

| | |
|--|--|
| Short Description | Masonry Cable Tie Mount, 1.24"L, .25" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 100/pkg |
| Global Part Name | MMB.5-PA66STHS-BK |
| Length L (Imperial) | 1.24 |
| Length L (Metric) | 31.5 |
| Fixation Method | with Fir Tree (Mounts) |
| Width W (Imperial) | 0.375 |
| Width W (Metric) | 9.5 |
| Cable Ties | T18 - T50 |
| Height H (Imperial) | .37 |
| Height H (Metric) | 9.40 |
| Cable Tie Width Max (Imperial) | 0.18 |
| Cable Tie Width Max (Metric) | 4.6 |
| Mounting Hole Diameter D (Imperial) | 0.25 |
| Mounting Hole Diameter D (Metric) | 6.35 mm |
| Mounting Hole Diameter D Max (Metric) | 6.35 |

| | |
|---------------------------------------|--|
| Material | Polyamide 6.6, super tough, heat stabilized (PA66STHS) |
| Material Shortcut | PA66STHS |
| Flammability | UL 94 HB |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |
| Content Unit(BMEcat) | pcs. |