

## Specification Sheet

Part Number: 151-00180



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Oval Fir Tree, 0.6-6.0 mm Panel Thick, 6.2x12.2 mm Hole Dia, PA66HIRHS, Black, 1000/pkg

**Article Number** 151-00180

**Type** YCCFT62x122

**Color** Black (BK)

**Quantity Per** pcs.

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Oval Fir Tree, 0.6-6.0 mm Panel Thick, 6.2x12.2 mm Hole Dia, PA66HIRHS, Black, 1000/pkg

**Global Part Name**

YCCFT62x122-PA66HIRHS-BK

**Length L (Imperial)**

0.83

**Length L (Metric)**

21.08

**Fixation Method**

Fir Tree for oval holes

**Width W (Imperial)**

0.63

**Width W (Metric)**

16.0

**Height H (Imperial)**

0.71

**Height H (Metric)**

18.0

**Panel Thickness Min (Imperial)**

0.02

**Panel Thickness Max (Imperial)**

0.24

**Panel Thickness Min (Metric)**

0.6

**Panel Thickness Max (Metric)**

6.0

**Mounting Hole Diameter D (Imperial)**

0.24 x 0.48

**Mounting Hole Diameter D (Metric)**

6.2 x 12.2 mm

**Mounting Hole Diameter D Min (Imperial)**

0.244

**Mounting Hole Diameter D Max (Imperial)**

0.48

**Mounting Hole Diameter D Max (Metric)** 12.2

**Material** Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut** PA66HIRHS

**Flammability** UL 94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988