

## Specification Sheet

Part Number: 151-00180



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Oval Fir Tree, 0.6-6.0 mm Panel Thick, 6.2x12.2 mm Hole Dia, PA66HIRHS, Black, 1000/pkg

**Article Number** 151-00180

**Type** YCCFT62x122

**Quantity Per** pcs.

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Oval Fir Tree, 0.6-6.0 mm Panel Thick, 6.2x12.2 mm Hole Dia, PA66HIRHS, Black, 1000/pkg

**Global Part Name** YCCFT62x122-PA66HIRHS

|  |                         |
|--|-------------------------|
| <b>Length L (Imperial)</b>                     | 0.83                    |
| <b>Length L (Metric)</b>                       | 21.08                   |
| <b>Fixation Method</b>                         | Fir Tree for oval holes |
| <b>Width W (Imperial)</b>                      | 0.63                    |
| <b>Width W (Metric)</b>                        | 16.0                    |
| <b>Height H (Imperial)</b>                     | 0.71                    |
| <b>Height H (Metric)</b>                       | 18.0                    |
| <b>Panel Thickness Min (Imperial)</b>          | 0.02                    |
| <b>Panel Thickness Max (Imperial)</b>          | 0.24                    |
| <b>Panel Thickness Min (Metric)</b>            | 0.6                     |
| <b>Panel Thickness Max (Metric)</b>            | 6.0                     |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.24 x 0.48             |
| <b>Mounting Hole Diameter D (Metric)</b>       | 6.2 x 12.2 mm           |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.244                   |
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.48                    |
| <b>Mounting Hole Diameter D Max (Metric)</b>   | 12.2                    |

|                                     |  |
|-------------------------------------|--|
| <b>Material</b>                     | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| <b>Material Shortcut</b>            | PA66HIRHS  |
| <b>Flammability</b>                 | UL 94 HB   |
| <b>Operating Temperature</b>        | -40°F to +221°F (-40°C to +105°C)                                |
| <b>Reach Compliant (Article 33)</b> | Yes  |
| <b>ROHS Compliant</b>               | Yes  |
| <b>Package Quantity (Imperial)</b>  | 1000   |
| <b>Package Quantity (Metric)</b>    | 1000   |
| <b>Customs Number</b>               | 3926909988   |