

## Specification Sheet

Part Number: 151-00194



HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip with Oval Arrowhead, 0.8-2.0mm Panel Thick, 7.0x12.0mm Hole Dia, PA66HIRHS, Black, 500/pkg

Article Number 151-00194

Type CCSFT7x12

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip with Oval Arrowhead, 0.8-2.0mm Panel Thick, 7.0x12.0mm Hole Dia, PA66HIRHS, Black, 500/pkg

Global Part Name	CCSFT7x12-PA66HIRHS-BK
Length L (Imperial)	0.63
Length L (Metric)	17.5
Fixation Method	Arrowhead
Width W (Metric)	17.5
Height H (Imperial)	0.69
Height H (Metric)	17.6
Panel Thickness Min (Imperial)	0.08
Panel Thickness Max (Imperial)	0.31
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.28 x 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm
Mounting Hole Diameter D Max (Metric)	12.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988