

## Specification Sheet

Part Number: 151-00194



Connector easily installed by simply pushing into place  
Connection can be released (non-destructive)

Arrowhead locks into place for secure fixing at all times

Conn. Clip w/Oval Arrowhead, 0.8-2.0mm Panel Thick, 7.0x12.0mm Hole Dia, PA66HIRHS, Black, 500/pkg

**Article Number** 151-00194

**Type** CCSFT7x12

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Oval Arrowhead, 0.8-2.0mm Panel Thick, 7.0x12.0mm Hole Dia, PA66HIRHS, Black, 500/pkg

**Global Part Name**

CCSFT7x12-PA66HIRHS-BK

**Length L (Imperial)**

0.63

**Length L (Metric)**

16.0

**Fixation Method**

Arrowhead for oval holes

**Height H (Imperial)**

0.69

**Height H (Metric)**

17.6

**Panel Thickness Min (Imperial)**

0.08

**Panel Thickness Max (Imperial)**

0.31

**Panel Thickness Min (Metric)**

0.8

**Panel Thickness Max (Metric)**

2.0

**Mounting Hole Diameter D (Imperial)**

0.28 - 0.47

**Mounting Hole Diameter D (Metric)**

7.0 x 12.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.275

**Mounting Hole Diameter D Max (Imperial)**

0.472

**Mounting Hole Diameter D Max (Metric)**

12.0

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)