

## Specification Sheet

Part Number: PBM0C2



Push-Button Cable Tie Mount, .25" Hole Dia, .12" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg

**Article Number** 151-00228

**Type** PBM

**Color** Black (BK)

**Features & Benefits**

- Push Mounts, when used with standard cable ties, provide a permanent bundling solution below a panel.
- The "button" style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

**Quantity Per** bag

**Product Description**

HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for installation below or underneath a panel. Designed for simple installation by pushing the mount through a pre-drilled hole. The low profile "button" style head is suitable in space constrained areas.

<b>Short Description</b>	Push-Button Cable Tie Mount, .25" Hole Dia, .12" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg
<b>Global Part Name</b>	PBM-PA66-BK
<b>Width W (Imperial)</b>	0.26
<b>Width W (Metric)</b>	6.6
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	.40
<b>Height H (Metric)</b>	10.20
<b>Cable Tie Width Max (Imperial)</b>	0.2
<b>Cable Tie Width Max (Metric)</b>	5.0
<b>Panel Thickness Max(Imperial)</b>	0.12
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.29
<b>Mounting Hole Diameter D (Metric)</b>	6.25 - 6.55 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.25
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.29

**Mounting Hole Diameter D Max (Metric)** 6.55

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**ROHS Complaint** Yes

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988