

Specification Sheet

Part Number: PBM9C2



Push Mounts, when used with standard cable ties, provide a permanent bundling solution below a panel.

The "button" style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

Push-Button Cable Tie Mount, .25" Hole Dia, .12" Max Panel, .2" Max Tie Width, PA66, Natural, 100/pkg

Article Number 151-00232

Type PBM

Color Natural (NA)

Quantity Per bag

Product Description HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for installation below or underneath a panel. Designed for simple installation by pushing the mount through a pre-drilled hole. The low profile "button" style head is suitable in space constrained areas.

Short Description Push-Button Cable Tie Mount, .25" Hole Dia, .12" Max Panel, .2" Max Tie Width, PA66, Natural, 100/pkg

Global Part Name PBM-PA66-NA

Width W (Imperial) 0.26

Width W (Metric) 6.6

Cable Ties T18 - T50

Height H (Imperial) .40

Height H (Metric) 10.20

Cable Tie Width Max (Imperial) 0.2

Cable Tie Width Max (Metric) 5.0

Panel Thickness Max (Imperial) 0.12

Panel Thickness Max (Metric) 3.0

Mounting Hole Diameter D (Imperial) 0.25 - 0.29

Mounting Hole Diameter D (Metric) 6.25 - 6.55 mm

Mounting Hole Diameter D Min (Imperial) 0.25

Mounting Hole Diameter D Max (Imperial) 0.29

Mounting Hole Diameter D Max (Metric) 6.55

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988