


## Specification Sheet

Part Number: MB40C2



Compact size fits most mounting applications.

Simple to install with a screw or rivet.

Single hole attachment with two-way entry for cable tie.

Screw Mount Cable Tie Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66, Black, 100/pkg

Article Number 151-00320

Type MB4

Color Black (BK)

Quantity Per bag

Product Description These cable tie mounts are compact in size. They are designed for simple yet robust installation. They pair with a cable tie for mounting applications including telecom equipment, switchgear and control cabinets.

Short Description Screw Mount Cable Tie Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66, Black, 100/pkg

Global Part Name MB4-PA66-BK

|                                       |                          |
|---------------------------------------|--------------------------|
| Length L (Imperial)                   | 1.12                     |
| Length L (Metric)                     | 28.5                     |
| Fixation Method                       | Screw Mounting and Rivet |
| Width W (Imperial)                    | 1.12                     |
| Width W (Metric)                      | 28.5                     |
| Cable Ties                            | T18 - 50                 |
| Height H (Imperial)                   | .19                      |
| Height H (Metric)                     | 4.80                     |
| Cable Tie Width Max (Imperial)        | 0.18                     |
| Cable Tie Width Max (Metric)          | 4.6                      |
| Mounting Hole Diameter D (Imperial)   | 0.18                     |
| Mounting Hole Diameter D (Metric)     | 4.6 mm                   |
| Mounting Hole Diameter D Max (Metric) | 4.6                      |
| Mounting Hole Centers (Imperial)      | 0.8                      |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material                      | Polyamide 6.6 (PA66)             |
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL                               |
| UL Recognized (US)            | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| Package Quantity (Imperial)   | 100                              |
| Package Quantity (Metric)     | 100                              |
| Customs Number                | 3926909988                       |