

Specification Sheet

Part Number: TM1SF10M4



Push Mounts, when used with standard cable ties, provide a permanent bundling solution.

The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

Push-Button Cable Tie Mount, 0.25" Hole Dia, 0.13" Max Panel, 0.2" Max Tie Width, PA66, White, 1000/pkg

Article Number 151-00328

Type TM1SF

Color White (WH)

Quantity Per bag

Product Description HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

Short Description Push-Button Cable Tie Mount, 0.25" Hole Dia, 0.13" Max Panel, 0.2" Max Tie Width, PA66, White, 1000/pkg

Global Part Name TM1SF-PA66-WH

| | |
|---------------------------------------|-----------|
| Length L (Imperial) | 0.62 |
| Length L (Metric) | 15.75 |
| Fixation Method | Arrowhead |
| Width W (Imperial) | 0.4 |
| Width W (Metric) | 10.2 |
| Cable Ties | T18 - T50 |
| Height H (Imperial) | .18 |
| Height H (Metric) | 4.60 |
| Cable Tie Width Max (Imperial) | 0.2 |
| Cable Tie Width Max (Metric) | 5.0 |
| Panel Thickness Min (Metric) | 3.40 |
| Panel Thickness Max (Metric) | 3.40 |
| Mounting Hole Diameter D (Imperial) | 0.25 |
| Mounting Hole Diameter D (Metric) | 6.3 mm |
| Mounting Hole Diameter D Max (Metric) | 6.35 |

| | |
|-------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

