

## Specification Sheet

Part Number: 151-00430



Connector Clip, Panel Thickness 1.5-4.0mm, PA66HIRHS, Black, 500/pkg

**Article Number** 151-00430

**Type** EC43

**Color** Black (BK)

**Features & Benefits**

- HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.
- Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.
- An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

**Quantity Per** bag

<b>Product Description</b>	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
<b>Short Description</b>	Connector Clip, Panel Thickness 1.5-4.0mm, PA66HIRHS, Black, 500/pkg
<b>Global Part Name</b>	EC43-PA66HIRHS-BK
<b>Length L (Imperial)</b>	0.95
<b>Length L (Metric)</b>	24.0
<b>Fixation Method</b>	Edge Clips
<b>Width W (Imperial)</b>	0.53
<b>Width W (Metric)</b>	13.4
<b>Panel Thickness Min(Imperial)</b>	0.06
<b>Panel Thickness Max(Imperial)</b>	0.16
<b>Panel Thickness Min (Metric)</b>	1.5
<b>Panel Thickness Max (Metric)</b>	4.0

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Use Conditions</b>	For Indoor Use Only
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	1.377