

## Specification Sheet

Part Number: HDM250HIRC2



Standard Torque Cable Tie Mount, Mtg Hole Dia. 0.25", Max Torque 115.0 in lbs, PA66HIRHSUV, Black, 100/pkg

|                                |   |
|--------------------------------|---|
| <b>Article Number</b>          | 151-00437   |
| <b>Type</b>                    | HDM25   |
| <b>Color</b>                   | Black (BK)  |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Mount and tie combination makes it easy to service bundles in the field.</li><li>• Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.</li><li>• Eliminates the needs for multiple sized fix diameter clamps.</li></ul> |
| <b>Quantity Per</b>            | bag   |
| <b>Product Description</b>     | These mounts contain a small tab inside the mounting hole to temporarily engage the threads, which allows assemblers to preinstall the mount on a stud before securing with a washer and a nut. For use with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.                               |

**Short Description**

Standard Torque Cable Tie Mount, Mtg Hole Dia. 0.25", Max Torque 115.0 in lbs, PA66HIRHSUV, Black, 100/pkg

**Global Part Name**

HDM25-PA66HIRHSUV-BK

**Length L (Imperial)**

1.41

**Length L (Metric)**

36.3

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.75

**Width W (Metric)**

19.3

**Height H (Imperial)**

0.66

**Height H (Metric)**

16.7

**Cable Tie Width Max (Imperial)**

0.50

**Cable Tie Width Max (Metric)**

12.7

**Mounting Hole Diameter D (Imperial)**

0.25

**Mounting Hole Diameter D (Metric)**

6.2 mm

**Mounting Hole Diameter D Min (Imperial)**

0.25

**Mounting Hole Diameter D Max (Imperial)**

0.25

**Mounting Hole Diameter D Max (Metric)**

6.2

|                                       |  |
|---------------------------------------|--|
| <b>Material</b>                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| <b>Material Shortcut</b>              | PA66HIRHSUV  |
| <b>Flammability</b>                   | UL 94 HB   |
| <b>Operating Temperature (Metric)</b> | -40°F to +230°F (-40°C to +110°C)  |
| <b>Maximum Torque (kgf-cm)</b>        | 132.5  |
| <b>Maximum Torque (lbf-ft)</b>        | 9.583  |
| <b>Reach Complaint(Article 33)</b>    | Yes  |
| <b>ROHS Complaint</b>                 | Yes  |
| <b>Package Quantity(Imperial)</b>     | 100  |
| <b>Package Quantity (Metric)</b>      | 100  |
| <b>Customs Number</b>                 | 3926909987   |
| <b>Content Unit(BMEcat)</b>           | pcs.   |
| <b>Weight (Imperial)</b>              | 0.00912  |

