

Specification Sheet

Part Number: HDM3120HIRH4

Mount and tie combination makes it easy to service bundles in the field. Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.



Eliminates the needs for multiple sized fix diameter clamps.

Standard Torque Cable Tie Mount, Mtg Hole Dia. 0.3125", Max Torque 115.0 in lbs, PA66HIRHSUV, Black, 500/pkg

Article Number 151-00440

Type HDM312

Color Black (BK)

Quantity Per bag

Product Description These mounts contain a small tab inside the mounting hole to temporarily engage the threads, which allows assemblers to preinstall the mount on a stud before securing with a washer and a nut. For use with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

Short Description Standard Torque Cable Tie Mount, Mtg Hole Dia. 0.3125", Max Torque 115.0 in lbs, PA66HIRHSUV, Black, 500/pkg

Global Part Name HDM312-PA66HIRHSUV-BK

Length L (Imperial) 1.43

Length L (Metric) 36.3

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 0.76

Width W (Metric) 19.3

Height H (Imperial) 0.66

Height H (Metric) 16.7

Cable Tie Width Max (Imperial) 0.50

Cable Tie Width Max (Metric) 12.7

Mounting Hole Diameter D (Imperial) 0.3125

Mounting Hole Diameter D (Metric) 7.8 mm

Mounting Hole Diameter D Min (Imperial) 0.3125

Mounting Hole Diameter D Max (Imperial) 0.3125

Mounting Hole Diameter D Max (Metric) 7.9

Stud Diameter (Metric) 7.9 mm

Stud Diameter (Imperial)	0.31
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Maximum Torque (kgf-cm)	132.5
Maximum Torque (lbf-ft)	9.583
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988