

## Specification Sheet

Part Number: ISO4X250H1



Design provides quick and easy assembly.  
Isolator mount dampens harmful vibrations on bundles  
Material is durable, chemical and abrasion resistant, and remains flexible in low temperatures.

Isolator Mount for separating 0.25" Tubing, 0.25" Max Bundle Diameter, TPV, Black, 500/pkg

**Article Number** 151-00455

**Type** ISO4X250

**Color** Black (BK)

**Quantity Per** carton

**Product Description** HellermannTyton's isolator mount is used to align and separate 1/4" tubing or brake lines. Easy to assemble, the isolator dampens vibrations and can be used with up to four brake lines. Mounting the isolator can be accomplished with HellermannTyton's standard cable ties, button head ties, and any of HellermannTyton's heavy equipment mounts. Mounting is optional, but recommended for long runs. The isolator is durable, chemical and abrasion resistant, and remains flexible in low temperatures.

<b>Short Description</b>	Isolator Mount for separating 0.25" Tubing, 0.25" Max Bundle Diameter, TPV, Black, 500/pkg
<b>Global Part Name</b>	ISO4X250-TPV-BK
<b>Width W (Imperial)</b>	0.92
<b>Width W (Metric)</b>	23.4
<b>Height H (Imperial)</b>	1.36
<b>Height H (Metric)</b>	34.5
<b>Material</b>	Thermoplastic vulcanized (TPV) rubber
<b>Material Shortcut</b>	TPV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-110°F to +347°F (-79°C to +175°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500

**Package Quantity (Metric)**

500

**Customs Number**

3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)