

## Specification Sheet

Part Number: 151-00677



Head design contains clamping rails to provide full circumferential compression around bundles. Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.76-5.75mm Panel Thick., 6.25-6.75mm Hole Dia., PA66HIRHS, Natural, 5000/ctn

**Article Number** 151-00677

**Type** CC08

**Color** Natural (NA)

**Quantity Per** carton

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Fir Tree, 0.76-5.75mm Panel Thick., 6.25-6.75mm Hole Dia., PA66HIRHS, Natural, 5000/ctn

**Global Part Name**

CC08-PA66HIRHS-NA

**Length L (Imperial)**

0.99

**Length L (Metric)**

25.2

**Fixation Method**

Fir Tree

**Width W (Imperial)**

0.78

**Width W (Metric)**

19.81

**Height H (Imperial)**

0.81

**Height H (Metric)**

20.55

**Panel Thickness Min (Imperial)**

0.03

**Panel Thickness Max (Imperial)**

0.23

**Panel Thickness Min (Metric)**

0.7

**Panel Thickness Max (Metric)**

5.75

**Mounting Hole Diameter D (Imperial)**

0.08 x 0.26

**Mounting Hole Diameter D (Metric)**

6.25 - 6.75 mm

**Mounting Hole Diameter D Min (Imperial)**

0.08

**Mounting Hole Diameter D Max (Imperial)**

0.26

**Mounting Hole Diameter D Max (Metric)** 6.75

**Material** Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut** PA66HIRHS

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988