

## Specification Sheet

Part Number: 151-00765



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.6-6.35 mm Panel Thick., 9.0x17.0 mm Hole Dia., PA66HIRHSUV, Black, 1000/ctn

**Article Number** 151-00765

**Type** CC09

**Color** Black (BK)

**Quantity Per** carton

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Fir Tree, 0.6-6.35 mm Panel Thick., 9.0x17.0 mm Hole Dia., PA66HIRHSUV, Black, 1000/ctn

**Global Part Name**

CC09-PA66HIRHSUV-BK

**Length L (Imperial)**

1.30

**Length L (Metric)**

33.05

**Fixation Method**

Fir Tree

**Width W (Imperial)**

0.85

**Width W (Metric)**

21.59

**Height H (Imperial)**

0.76

**Height H (Metric)**

19.4

**Panel Thickness Min (Imperial)**

0.019

**Panel Thickness Max (Imperial)**

0.252

**Panel Thickness Min (Metric)**

0.5

**Panel Thickness Max (Metric)**

6.4

**Mounting Hole Diameter D (Imperial)**

0.35 x 0.67

**Mounting Hole Diameter D (Metric)**

9.0 x 17.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.35

**Mounting Hole Diameter D Max (Imperial)**

0.67

**Mounting Hole Diameter D Max (Metric)** 17.0

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988