

## Specification Sheet

Part Number: 151-00775



HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.

HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Conn. Clip w/Arrowhead, 1.7-2.3 mm Panel Thick., 6.3-6.7 mm Hole Dia., PA66HIRHS, Black, 5000/box

**Article Number** 151-00775

**Type** CCSFT6.5

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HellermannTyton connector clips for oval holes are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The arrowhead locks firmly into place when inserted into the hole palpably and ensures a secure attachment at all times.

**Short Description** Conn. Clip w/Arrowhead, 1.7-2.3 mm Panel Thick., 6.3-6.7 mm Hole Dia., PA66HIRHS, Black, 5000/box

**Global Part Name** CCSFT6.5-PA66HIRHS-BK

**Technical Description** Connector Clip, Black

**Length L (Imperial)** 0.9

**Length L (Metric)** 23.0

**Fixation Method** Arrowhead (Small Mount)

**Height H (Imperial)** 0.48

**Height H (Metric)** 12.1

**Panel Thickness Min (Imperial)** 0.07

**Panel Thickness Max (Imperial)** 0.09

**Panel Thickness Min (Metric)** 1.7

**Panel Thickness Max (Metric)** 2.3

**Mounting Hole Diameter D (Imperial)** 0.25 - 0.26

**Mounting Hole Diameter D (Metric)** 6.3 - 6.7 mm

**Mounting Hole Diameter D Min (Imperial)** 0.25

**Mounting Hole Diameter D Max (Imperial)** 0.26

**Mounting Hole Diameter D Max (Metric)** 6.7

<b>Disc Diameter (Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Customs Number</b>	3926909988