

## Specification Sheet

Part Number: 151-00785



Connector Clip w/Fir Tree, 0.7 - 4.0 mm Panel Thickness, 6.0 - 6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box

**Article Number**

151-00785

**Type**

CCFT6LG

**Color**

Black (BK)

**Features & Benefits**

- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

**Quantity Per**

bag

**Product Description**

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

<b>Short Description</b>	Connector Clip w/Fir Tree, 0.7 - 4.0 mm Panel Thickness, 6.0 - 6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box
<b>Global Part Name</b>	CCFT6LG-PA66HIRHS-BK
<b>Technical Description</b>	Connector Clip, Black
<b>Fixation Method</b>	Fir Tree
<b>Panel Thickness Min(Imperial)</b>	0.028
<b>Panel Thickness Max(Imperial)</b>	0.16
<b>Panel Thickness Min (Metric)</b>	0.7
<b>Panel Thickness Max (Metric)</b>	4.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.0 - 6.7 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.7
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS

<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.8