

## Specification Sheet

Part Number: 151-00835



Connector Clip, 0.7 - 1.3 mm Panel Thickness, 6.2 x 12.2 mm Hole Dia, PA66HIRHS, Black, 10,000/box

<b>Article Number</b>	151-00835
<b>Type</b>	YCCKSFT62x122PT0.7-1.3
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Head design contains clamping rails to provide full circumferential compression around bundles.</li><li>• Bent tail allows for quick insertion into head.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
<b>Short Description</b>	Connector Clip, 0.7 - 1.3 mm Panel Thickness, 6.2 x 12.2 mm Hole Dia, PA66HIRHS, Black, 10,000/box

**Global Part Name**

YCKKSFT62x122PT0.7-1.3-PA66HIRHS-BK

**Technical Description**

Connector Clip, Black

**Panel Thickness Min(Imperial)**

0.028

**Panel Thickness Max(Imperial)**

0.05

**Panel Thickness Min (Metric)**

0.7

**Panel Thickness Max (Metric)**

1.3

**Mounting Hole Diameter D (Imperial)**

0.24 - 0.48

**Mounting Hole Diameter D (Metric)**

6.2 x 12.2 mm

**Mounting Hole Diameter D Min (Imperial)**

0.24

**Mounting Hole Diameter D Max (Imperial)**

0.48

**Mounting Hole Diameter D Max (Metric)**

12.2

**Material**

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut**

PA66HIRHS

**Operating Temperature (Metric)**

-40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

10000

**Package Quantity (Metric)**

10000

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.