

Specification Sheet

Part Number: 151-00942



Bundling Clip w Fir Tree, 1.5"L, .02"-.20" Panel Thick, .25"-.28" Hole Dia, PA66HIRHS, Bk, 12,000/box

Article Number	151-00942
Type	TC4FT6LG
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.• Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.• HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.
Quantity Per	carton

Product Description

HellermannTyton connector clips, for oval holes, are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The fir tree locks into place when inserted into the hole palpably and ensures a secure fixing at all times.

Short Description	Bundling Clip w Fir Tree, 1.5"L, .02"-.20" Panel Thick, .25"-.28" Hole Dia, PA66HIRHS, Bk,12,000/box
Global Part Name	TC4FT6LG-PA66HIRHS-BK
Length L (Imperial)	1.5
Length L (Metric)	37.0
Fixation Method	Fir Tree
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.20
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	5.1
Mounting Hole Diameter D (Imperial)	0.25 - 0.28
Mounting Hole Diameter D (Metric)	6.3 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut

PA66HIRHS

Operating Temperature (Metric)

-40°F to +221°F (-40°C to +105°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

14000

Package Quantity (Metric)

14000

Customs Number

3926909988