

Specification Sheet

Part Number: 151-01022



LOC Locking Clamp, 15-19 mm, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Article Number

151-01022

Type

LOC15-19FT6LG

Color

Black (BK)

Features & Benefits

- The 360 degree locking enclosure dynamically fits a range of bundle sizes.
- Clamp can be opened for bundle maintenance.
- Low-profile release tab won't interfere with bundle or nearby routing.
- Fir tree demonstrates easy insertion with high extraction resistance.

Quantity Per

carton

Product Description

The LOC with Round Fir Tree features HellermannTyton's unique retention clamp attached to a 6.5 mm fir tree. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel.

| | |
|---------------------------------------|---------------------------------------------------------------------------------|
| Short Description | LOC Locking Clamp, 15-19 mm, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 1000/ctn |
| Global Part Name | LOC15-19FT6LG-PA66HIRHSUV-BK |
| Length L (Imperial) | 1.24 |
| Length L (Metric) | 31.6 |
| Fixation Method | Fir Tree |
| Width W (Imperial) | 0.47 |
| Width W (Metric) | 12.0 |
| Bundle Diameter Min (Imperial) | 0.59 |
| Bundle Diameter Min (Metric) | 15.0 |
| Bundle Diameter Max (Imperial) | 0.75 |
| Bundle Diameter Max (Metric) | 19.0 |
| Height H (Imperial) | 1.87 |
| Height H (Metric) | 47.5 |
| Depth D (imperial) | 0.47 |
| Depth D (metric) | 12.0 |
| Panel Thickness Min(Imperial) | 0.02 |

| | |
|------------------------------------------------|--------------------------------------------------------------------------|
| Panel Thickness Max(Imperial) | 0.32 |
| Panel Thickness Min (Metric) | 0.60 |
| Panel Thickness Max (Metric) | 8.25 |
| Mounting Hole Diameter D (Imperial) | 0.25 " HEX; 0.26 |
| Mounting Hole Diameter D (Metric) | 6.1 - 6.9 mm 6.35 mm (hexagonal) |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Metric) | 6.9 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +230°F (-40°C to +110°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |

| | |
|-----------------------------------|------------|
| Package Quantity(Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909987 |
| Content Unit(BMEcat) | pcs. |
| Weight (Metric) | 3.31 |
| Weight (Imperial) | 0.12 |