

Specification Sheet

Part Number: 151-01109

The 90-degree configuration of this mini channel creates a solution for routing a wire harness around a corner.

Design allows the mini channel to be used with a wide range of panel thicknesses and hole diameters.



Disc prevents rattling in high-vibration applications and protects against leakage and debris.

Mini Channel, 1.38" Long, 90° Angle, Arrowhead, PA66HIRHSUV, Black, 4000/pkg

Article Number 151-01109

Type BC90AH2

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Bundling Clips create a solution that allows the harness to be routed around a corner, and fixated into the panel at this location.

Short Description Mini Channel, 1.38" Long, 90° Angle, Arrowhead, PA66HIRHSUV, Black, 4000/pkg

Global Part Name BC90AH2-PA66HIRHSUV-BK

Length L (Imperial)	0.98
Length L (Metric)	25.0
Fixation Method	Arrowhead
Width W (Imperial)	0.06
Width W (Metric)	1.5
Height H (Imperial)	0.93
Height H (Metric)	23.6
Diameter D (Imperial)	0.50
Diameter D (Metric)	12.58
Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	1.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.2 - 6.8 mm
Mounting Hole Diameter D Max (Metric)	6.8

Disc Diameter (Metric)	12.58
Disc Diameter (Imperial)	0.50
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988