

Specification Sheet

Part Number: 151-01136



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.51-6.5mm Panel Thick., 8.0x15.0 mm Hole Dia., PA66HIRHSUV, Black, 4000/ctn

Article Number 151-01136

Type CC12

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Conn. Clip w/Fir Tree, 0.51-6.5mm Panel Thick., 8.0x15.0 mm Hole Dia., PA66HIRHSUV, Black, 4000/ctn

Global Part Name

CC12-PA66HIRHSUV-BK

Length L (Imperial)

1.00

Length L (Metric)

25.5

Fixation Method

Fir Tree

Width W (Imperial)

0.72

Width W (Metric)

18.29

Height H (Imperial)

0.87

Height H (Metric)

22.2

Panel Thickness Min (Imperial)

0.02

Panel Thickness Max (Imperial)

0.26

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

6.5

Mounting Hole Diameter D (Imperial)

0.31 x 0.59

Mounting Hole Diameter D (Metric)

8.0 x 15.0 mm

Mounting Hole Diameter D Min (Imperial)

0.31

Mounting Hole Diameter D Max (Imperial)

0.59

Mounting Hole Diameter D Max (Metric) 15.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 4000

Package Quantity (Metric) 4000

Customs Number 3926909988