

## Specification Sheet

Part Number: 151-01224



Mount and tie combination makes it easy to service bundles in the field

Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments

Eliminates the needs for multiple sized fix diameter clamps

High Torque Mount, 0.375" Mounting Hole Dia, 114.0 lb/ft Max Torque, PA66HIRHSUV, Black, 500/pkg

Article Number 151-01224

Type HDM400

Color Black (BK)

Quantity Per bag

Product Description This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

Short Description High Torque Mount, 0.375" Mounting Hole Dia, 114.0 lb/ft Max Torque, PA66HIRHSUV, Black, 500/pkg

Global Part Name HDM400-PA66HIRHSUV-BK

|                                       |                          |
|---------------------------------------|--------------------------|
| Minimum Tensile Strength (Imperial)   | 120                      |
| Minimum Tensile Strength (Metric)     | 533                      |
| Length L (Imperial)                   | 1.85                     |
| Length L (Metric)                     | 47.0                     |
| Fixation Method                       | Screw Mounting and Rivet |
| Width W (Imperial)                    | 0.98                     |
| Width W (Metric)                      | 25.0                     |
| Height H (Imperial)                   | 0.81                     |
| Height H (Metric)                     | 20.7                     |
| Cable Tie Width Max (Imperial)        | 0.5                      |
| Cable Tie Width Max (Metric)          | 12.7                     |
| Mounting Hole Diameter D (Imperial)   | 0.41                     |
| Mounting Hole Diameter D (Metric)     | 10.29 mm                 |
| Mounting Hole Diameter D Max (Metric) | 10.29                    |
| Stud Diameter (Metric)                | 10.0 mm                  |
| Stud Diameter (Imperial)              | 0.375                    |

|                              |  |
|------------------------------|--|
| Material                     | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut            | PA66HIRHSUV  |
| Flammability                 | UL 94 HB   |
| UV Resistant (Yes/No)        | Yes  |
| Use Conditions               | For Indoor and Outdoor Use   |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)  |
| Maximum Torque (kgf-cm)      | 1576.0   |
| Maximum Torque (lbf-ft)      | 114.0  |
| Reach Compliant (Article 33) | Yes  |
| ROHS Compliant               | Yes  |
| Package Quantity (Imperial)  | 500  |
| Package Quantity (Metric)    | 500  |
| Customs Number               | 3926909988   |

