


Specification Sheet

Part Number: 151-01238



Standoff Bundling Clip, 1.97" Long, Panel Thickness 0.02–0.27", PA66HIRHS, Natural, 1500/carton

Article Number	151-01238
Type	SOC12FTOVAL
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none">•Clip can be installed by hand – no need for hardware or tools.•Design provides low insertion and high extraction force, for simple, secure performance.•Clip keeps bundle away from areas that could cause damage due to rubbing.
Quantity Per	carton

Product Description

Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing.

Short Description	Standoff Bundling Clip, 1.97" Long, Panel Thickness 0.02–0.27", PA66HIRHS, Natural, 1500/carton
Global Part Name	SOC12FTOVAL-PA66HIRHS-NA
Length L (Imperial)	1.97
Length L (Metric)	50.0
Offset Length(Imperial)	1.26
Offset Length(Metric)	32.0
Fixation Method	Fir Tree for oval holes
Height H (Imperial)	0.79
Height H (Metric)	20.0
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.27
Panel Thickness Min (Metric)	0.51
Panel Thickness Max (Metric)	6.86
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm 7.0 x 12.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24

Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1500
Package Quantity (Metric)	1500
Customs Number	3926909987
Content Unit(BMEcat)	pcs.